### **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

# **Listing of Claims:**

1. (Currently Amended) A computer-implemented method of improving performance in a Java computer application program executable by a Java virtual machine (JVM), comprising the steps of:

obtaining information associated with garbage collection; and

deducing changes in performance that will result from modifying the Java computer application program;

wherein a cost of garbage collection to program performance of a modified version of the Java computer application program is estimated by the computer-implemented method using a duration of an average garbage collection event and a frequency of occurrence of particular garbage collection events, wherein the duration depends on an amount of garbage that must be cleaned up, an algorithm used to do collecting or copying, a heap compaction, a cost of reconciling object references that are moved, and a number of finalizers that must be executed, and wherein the frequency depends on a rate of object creation, heap fragmentation, size of the heap, and a garbage collection policy;

wherein the Java computer application program is changed by reducing memory from a footprint of the Java computer application program, wherein given an amount of memory to be reduced from the footprint (m), a total duration for a run (d), and how much of the run is spent in garbage collection (g), a number of additional transactions that can be computed during the run is determined according to:

y = function (m, t, g, d, f), where

<u>t</u> is current computed throughput of the Java computer application program in transactions/second, f is average memory footprint of the Java computer application program during duration d, and y is the number of additional transactions gained after reducing the memory footprint of the Java computer application program to (f-m) during the total duration d.

- 2-7. (Cancelled)
- 8. (Currently Amended) The method of claim [[7]] 1, wherein the information associated with garbage collection is obtained from a verbosegc.

## 9. (Cancelled)

10. (Currently Amended) A computer system capable of running a Java application program by a Java virtual machine (JVM), comprising:

a garbage heap associated with garbage collection events, wherein garbage collection events have an average duration and frequency; and

instructions for estimating changes in performance resulting from modification of the Java application program using information obtained about the garbage collection events;

wherein a cost of garbage collection to program performance of a modified version of the Java application program is estimated by the computer system using a duration of an average garbage collection event and a frequency of occurrence of particular garbage collection events, wherein the duration depends on an amount of garbage that must be cleaned up, an algorithm used to do collecting or copying, a heap compaction, a cost of reconciling object references that are moved, and a number of finalizers that must be executed, and wherein the frequency depends on a rate of object creation, heap fragmentation, size of the heap, and a garbage collection policy;

wherein the Java application program is changed by deducting memory from a footprint of the Java application program, wherein given an amount of memory to be deducted from the footprint (m), a total duration for a run (d), and how much of the run is spent in garbage collection (g), a number of additional transactions that can be computed during the run is determined according to:

#### y = function (m, t, g, d, f), where

<u>t</u> is current computed throughput of the Java computer application program in transactions/second, f is average memory footprint of the Java computer application program during duration d, and y is the number of additional transactions gained after reducing the memory footprint of the Java computer application program to (f - m) during the total duration d.

#### 11-15. (Cancelled)

16. (Currently Amended) The method of claim [[15]] <u>10</u>, wherein the information associated with garbage collection is obtained from a verbosegc.

17. (Currently Amended) A computer program product in a computer readable medium for improving performance in a Java computer application program executable by a Java virtual machine (JVM), comprising:

first instructions for obtaining information associated with garbage collection; and second instructions for deducing changes in performance that will result from modifying the Java computer application program, wherein a cost of garbage collection to program performance of the Java computer application program is estimated by the computer program product using a duration of an average garbage collection event and a frequency of occurrence of particular garbage collection events, wherein the duration depends on an amount of garbage that must be cleaned up, an algorithm used to do collecting or copying, a heap compaction, a cost of reconciling object references that are moved, and a number of finalizers that must be executed, and wherein the frequency depends on a rate of object creation, heap fragmentation, size of the heap, and a garbage collection policy;

wherein the Java computer program is changed by deducting memory from a footprint of the Java computer application program, wherein given an amount of memory to be deducted from the footprint (m), a total duration for a run (d), and how much of the run is spent in garbage collection (g), a number of additional transactions that can be computed during the run is determined according to:

y = function (m, t, g, d, f), where

t is current computed throughput of the Java computer application program in transactions/second, t is average memory footprint of the Java computer application program during duration t, and t is the number of additional transactions gained after reducing the memory footprint of the Java computer application program to t0 during the total duration t1.

18-22. (Cancelled)

23. (Currently Amended) The method of claim [[22]] <u>17</u>, wherein the information associated with garbage collection is obtained from a verbosegc.